


## Roulement à rouleaux NA4907UU-JTEKT - NA4907UU-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4907uu-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
F <sub>w</sub>	d	D	B	B <sub>1</sub>	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.		Without inner ring	
42	35	55	20	21	29.0	40.9	4 700		—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
		d <sub>i</sub>	D <sub>i</sub>	r <sub>e</sub>	Without inner ring	With inner ring				
		max.	max.	max.	—	0.173	IRM354221			
		<b>NA4907UU</b>			39	51	0.6			

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483108
Diam. intérieur	35 mm
Diam. extérieur	55 mm
Épaisseur	20 mm
Poids	173 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE