


Roulement à rouleaux NA5907-JTEKT - NA5907-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na5907-jtekt>

Machined ring needle roller bearings  **Koyo**
F_w 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|----|----|----|----------------|-------------------------|-----------------|--|-------------|--------------------|-----------|
| F _w | d | D | B | B ₁ | C _r | C ₁₀ | Oil lub. | Grease lub. | Without inner ring | |
| 42 | 35 | 55 | 27 | — | 42.9 | 67.6 | 11 000 | — | — | |
| Mounting dimensions (mm) | | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | |
| NA5907 | | | | | 39 | 51 | 0.6 | 0.138 | 0.225 | IRM354227 |

[Note] 1) Limiting speeds of bearing number NA49, LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952483160 |
| Diam. intérieur | 35 mm |
| Diam. extérieur | 55 mm |
| Épaisseur | 27 mm |
| Poids | 225 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE