


Roulement à rouleaux NQ45-30-JTEKT - NQ45-30-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq45-30-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	Without inner ring	
45	40	55	30	40.9	86.1	10 000	NQ45/30		
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d _i min.	D _i max.	r _a max.	0.138	0.214				
	44	51	0.8						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483214
Diam. intérieur	45 mm
Diam. extérieur	55 mm
Épaisseur	30 mm
Poids	138 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE