


## Roulement à rouleaux NQI40-30-JTEKT - NQI40-30-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nqi40-30-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$B_1$	$C_r$	$C_{10}$	Oil lub.	Grease lub.	Without inner ring	With inner ring
45	40	55	30	—	40.9	86.1	10 000		—	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
		With inner ring	$d_a$ max.	$D_a$ max.	$r_a$ max.	Without inner ring	With inner ring			
		NQI40/30	44	51	0.8	0.138	0.214			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	605790188039
Diam. intérieur	40 mm
Diam. extérieur	55 mm
Épaisseur	30 mm
Poids	214 g
Conditionnement	-

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE