


Roulement à rouleaux NA4908-JTEKT - NA4908-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4908-jtekt>

Machined ring needle roller bearings 
F_w 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----|----|----|-------------------------|-----------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C ₁₀ | Oil lub. | Without inner ring | |
| 48 | 40 | 62 | 22 | 32.6 | 58.5 | 9 700 | — | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | | | |
| NA4908 | | | | 44 | 58 | 0.157 | 0.249 | IRM404822 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952483283 |
| Diam. intérieur | 40 mm |
| Diam. extérieur | 62 mm |
| Épaisseur | 22 mm |
| Poids | 249 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE