

Roulement à rouleaux NQ50-20A-JTEKT - NQ50-20A-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq50-20a-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
50	—	62	20	—	24.8	46.0	9 400	NQ50/20A
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d _i min.	D _i max.	r _e max.	Without inner ring	With inner ring		
		—	58	0.6	0.126	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483344
Diam. intérieur	50 mm
Diam. extérieur	62 mm
Épaisseur	20 mm
Poids	126 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE