


Roulement à rouleaux NA4909UU-JTEKT - NA4909UU-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4909uu-jtekt>

Machined ring needle roller bearings

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speed ¹⁾ (min ⁻¹)	Bearing No.
F_w	d	D	B	B_1	C_r	C_{10}	Oil lub.	Without inner ring
52	45	68	22	23	37.7	56.8	3 800	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d_a	D_a	r_a	Without inner ring	With inner ring		
NA4909UU		49	64	0.6	—	0.285	IRM455223	

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3616060465689
Diam. intérieur	45 mm
Diam. extérieur	68 mm
Épaisseur	22 mm
Poids	285 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE