


Roulement à rouleaux NA5909-JTEKT - NA5909-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na5909-jtekt>

Machined ring needle roller bearings

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	B_{min}	C_r	C_{0r}	Oil lub.	Grease lub.	Without inner ring
52	45	68	30	—	58.9	101.0	8 800	—	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		With inner ring	d_a min.	D_a max.	r_a max.	Without inner ring	With inner ring		
		NA5909	49	64	0.6	0.252	0.365	IRM455230	

[Note] 1) Limiting speeds of bearing number NA49, LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483429
Diam. intérieur	45 mm
Diam. extérieur	68 mm
Épaisseur	30 mm
Poids	365 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE