


## Roulement à rouleaux NQ536825A-JTEKT - NQ536825A-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/nq536825a-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10</sub>	Oil lub.	Without inner ring	
53	—	68	24.5	—	47.1	81.7	8 700	<b>NQ536825A</b>
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
d <sub>a</sub> min.	D <sub>a</sub> max.	r <sub>a</sub> max.	—	64	0.6	0.207	—	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483450
Diam. intérieur	53 mm
Diam. extérieur	68 mm
Épaisseur	24.5 mm
Poids	207 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE