


## Roulement à rouleaux RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/rna49-48r-jtekt>

### Machined ring needle roller bearings

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
55	—	70	22	—	46.9	76.5	8 300	RNA49/48R
		Mounting dimensions (mm)			( roller ) Mass (kg)		( roller )	
		With inner ring	$d_a$ min.	$D_a$ max.	$r_a$ max.	Without inner ring	With inner ring	Applicable inner ring No.
		—	66	66	0.6	0.174	—	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483481
Diam. intérieur	55 mm
Diam. extérieur	70 mm
Épaisseur	22 mm
Poids	174 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE