


Roulement à rouleaux RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/rna49-48r-jtekt>

Machined ring needle roller bearings

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-----|--------------------------|-------|-------------------------|----------------------|--|--------------------------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Without inner ring | |
| 55 | — | 70 | 22 | — | 46.9 | 76.5 | 8 300 | RNA49/48R |
| | | Mounting dimensions (mm) | | | (roller) Mass (kg) | | (roller) Applicable inner ring No. | |
| With inner ring | | d_a | D_a | r_a | Without inner ring | With inner ring | | |
| | | min. | max. | max. | — | — | — | |
| | | — | 66 | 0.6 | 0.174 | — | — | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952483481 |
| Diam. intérieur | 55 mm |
| Diam. extérieur | 70 mm |
| Épaisseur | 22 mm |
| Poids | 174 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE