


## Roulement à rouleaux NA4910R-JTEKT - NA4910R-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4910r-jtekt>

### Machined ring needle roller bearings

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$B_r$	$C_r$	$C_{10}$	Oil lub.	—	Without inner ring	
58	50	72	22	—	48.0	80.0	7 900	—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
NA4910R					54	68	0.5	0.172	0.276	IRM505822

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483559
Diam. intérieur	50 mm
Diam. extérieur	72 mm
Épaisseur	22 mm
Poids	276 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE