


## Roulement à rouleaux NA4911R-JTEKT - NA4911R-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4911r-jtekt>

### Machined ring needle roller bearings

$F_w$  29 – 37 mm

With inner ring



| Boundary dimensions (mm) |    |                          |            |            | Basic load ratings (kN) |                    | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |             | Bearing No.        |
|--------------------------|----|--------------------------|------------|------------|-------------------------|--------------------|--|-------------|--------------------|
| $F_w$                    | d  | D                        | B          | $B_r$      | $C_r$                   | $C_{10}$           | Oil lub.   | Grease lub. | Without inner ring |
| 63                       | 55 | 80                       | 25         | —          | 58.4                    | 99.0               | 7 300  | —           | —                  |
|                          |    | Mounting dimensions (mm) |            |            | (Refer.) Mass (kg)      |                    | (Refer.) Applicable inner ring No.                 |             |                    |
|                          |    | With inner ring          | $d_a$ max. | $D_a$ max. | $r_a$ max.              | Without inner ring | With inner ring                                    |             |                    |
|                          |    | NA4911R                  | 60         | 75         | 1                       | 0.260              | 0.401  | IRM55G325   |                    |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952483665 |
| Diam. intérieur | 55 mm         |
| Diam. extérieur | 80 mm         |
| Épaisseur       | 25 mm         |
| Poids           | 401 g         |
| Conditionnement | 1             |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE