


Roulement à rouleaux NA4918-JTEKT - NA4918-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4918-jtekt>

Machined ring needle roller bearings 
F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C ₁₀	Oil lub.	Without inner ring	
105	90	125	35	111.0	238.0	4 400	—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d _a max.	D _a max.	r _a max.	Without inner ring	With inner ring		
NA4918		96.5	118.5	1	0.695	1.31	IRM9010535	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952484105
Diam. intérieur	90 mm
Diam. extérieur	125 mm
Épaisseur	35 mm
Poids	1310 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE