


Roulement à rouleaux NA4922-JTEKT - NA4922-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/na4922-jtekt>

Machined ring needle roller bearings 
F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	B ₁	r	C _r	C ₁₀	Oil lub.	Without inner ring	Without inner ring
125	110	150	40	—	1.1	149.0	317.0	3 700	—	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
		With inner ring	d ₁ min.	D ₁ max.	r ₁ max.	Without inner ring	With inner ring			
		NA4922	116.5	143.5	1	1.17	2.01	IRM11012540		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952484266
Diam. intérieur	110 mm
Diam. extérieur	150 mm
Épaisseur	40 mm
Poids	2010 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE