

Roulement à rouleaux RNA5924-JTEKT - RNA5924-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/rna5924-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
135	120	165	60	244.0	564.0	3 400	RNA5924	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d ₁ min.	D ₁ max.	r ₁ max.	Without inner ring	With inner ring		
		126.5	158.5	1	2.43	3.80	IRM12013560	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952484310
Diam. intérieur	135 mm
Diam. intérieur	5.315" inch
Diam. extérieur	165 mm
Diam. extérieur	6.496" inch
Epaisseur	60 mm
Epaisseur	2.362" inch
Poids	2430 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE