


Roulement à aiguilles NQI12-16D-JTEKT - NQI12-16D-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nqi12-16d-jtekt>

Machined ring needle roller bearings ————— Koyo
F_w 29 – 37 mm

With inner ring



F _w	Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
	d	D	B	B _s	r _{min}	C _r	C _{10r}	Oil lub.	Grease lub.		
16	12	24	16	16	0.3	10.9	15.2	28 000		—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
		With inner ring			Without inner ring	With inner ring					
		ds	Ds	rs	Without inner ring	With inner ring					
		min.	max.	max.	—	0.036					
		NQI12/16D			14	22	0.3				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952488974
Diam. intérieur	12 mm
Diam. extérieur	24 mm
Épaisseur	16 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE