

Rotule GE POS8-PU-DUNLOP - POS8-PU-DUNLOP

https://www.123roulement.be/roulement-palier/rotule/ge/pos8-pu-dunlop

MALE ROD ENDS

MH SERIES: MH - MHS - MH SS

Description:
MH series is our 3-piece unique internationally patented range of male rod ends incorporating a polyurethane bearing race that provides ultra smooth operation. A nitronic surface protected ball with a PTFE lubricant provide superior shock load and extended wear properties, combined with excellent chemical and corrosion resistance. The unique innovative captive body design prevents detachment through excessive axial loads. For optimum performance, ensure that the rod end is mounted with the moulded lettering facing away from the direction of pull.

Material Specifications:
Housing: Steel 230M07PB zinc plated and clear trivalent passivate. Race: Polyurethane. Ball: 230M07PB nitronic finish. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303C. Lubricant: UniTor Oil.

Features:
Metric & imperial sizes
Ultra low friction
High shock loads
Extended wear life
No maintenance
Serrated option

Possible Applications:
Light to medium
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control
Safety features

Temperature Range:
-40°C to + 80°C

Specification:
ELV & RoHS compliant

Housing: Steel 230M07PB Zinc Plated and Clear Trivalent Passivate **Ball:** Steel 230M07PB - Nitronic Surface Protection

Race: Polyurethane **Lubricant:** UniTor Oil

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MH-MDB		8	M8x1.25	12	9.80	24	42	25	10.35	17,602

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060473196
Diam. intérieur	8 mm
Diam. intérieur	0.315" inch
Diam. extérieur	24 mm
Diam. extérieur	0.945" inch
Epaisseur	9 mm
Epaisseur	0.354" inch
Type	GE
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE