


Douille à aiguilles BA1716-ZOH-IKO - BA1716-ZOH-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/ba1716-zoh-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BA--Z BHA--Z

Shaft dia. mm (inch)	Standard			Closed end			Mass (Ref.) g			Identification number			Greas retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	
26.988 (1 1/16)	---	---	---	---	BA 1716 Z	37	---	---	---	---	---	---	---

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Ball dynamic load rating C _d	Ball static load rating C ₀	Allowable rotational speed(*) rpm	Assembled inner ring
F _w	D	C	Shaft dia. h8 Max.	Housing bore dia. J7 Min.	Max.	Min.				
26.988 1 5/16	33.338 1 1/8	25.40 1.000 2.8	26.988	26.975	33.352	33.327	20 000	38 900	14 000	---

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172835
Diam. intérieur	26.99 mm
Diam. intérieur	1 1/16" inch
Diam. extérieur	33.34 mm
Diam. extérieur	1 5/16" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Poids	10 g
Conditionnement	-
Norme	Sans norme

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE