


Douille à aiguilles BAM1016-IKO - BAM1016-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam1016-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
15.875 (5/8)	—	—	—	—	—	—	—	BAM 1016	18.4	—	—
Boundary dimensions		mm (inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	N	N	N	N	rpm	IRB 716
15.875 / ₄	20.638 / ₂	25.40(1.000)	1.3	15.875 Max.	15.864 Min.	20.650 Max.	20.629 Min.	12 300	20 800	25 000	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172927
Diam. intérieur	15.88 mm
Diam. intérieur	5/8" inch
Diam. extérieur	20.64 mm
Diam. extérieur	13/16" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE