


## Douille à aiguilles BAM107-IKO - BAM107-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam107-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
15.875 (5/8)	—	—	—	—	—	<b>BAM 107</b>	—	8.7	—		
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring				
F <sub>w</sub>	D	C	b <sub>2</sub>	Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm			
15.875	20.638	11.13	1.3	15.875	15.864	20.650	20.629	5 040	6 660	25 000	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172941
Diam. intérieur	15.88 mm
Diam. intérieur	5/8" inch
Diam. extérieur	20.64 mm
Diam. extérieur	13/16" inch
Epaisseur	11.13 mm
Epaisseur	0.438" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE