


Douille à aiguilles BAM108-IKO - BAM108-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam108-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
15.875 (5/8)	—	—	—	—	—	BAM 108	9.9	—	—
Boundary dimensions mm (inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed(*)	Assembled inner ring
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	C	C_0	rpm	
15.875	20.638	12.70	1.3	15.875 Max. Min.	15.864 Max. Min.	20.650 20.629	5 420 7 310	25 000	IRB 68-1

Notes*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952172958
Diam. intérieur	15.88 mm
Diam. intérieur	5/8" inch
Diam. extérieur	20.64 mm
Diam. extérieur	13/16" inch
Epaisseur	12.7 mm
Epaisseur	1/2" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE