


## Douille à aiguilles BAM1216-IKO - BAM1216-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam1216-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end											
19.050 (3/4)	—	—	—	—	—	—	—	—	—	—	<b>BAM 1216</b>	28.5	—	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring		
F <sub>w</sub>	D	C	h <sub>6</sub>	Shaft dia. Max.	Housing bore dia. Min.						
19.050	25.400	25.400(1.000)	1.3	19.050	19.037	25.412	25.391	16 300	26 500	20 000	<b>IRB 816-1</b>

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173030
Diam. intérieur	19.05 mm
Diam. extérieur	25.4 mm
Épaisseur	25.4 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE