


Douille à aiguilles BAM1314-IKO - BAM1314-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam1314-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
20.638 ($\frac{13}{16}$)	—	—	—	—	—	—	BAM 1314	27	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	r_2 Max.	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm	IRB 914
20.638 $\frac{3}{5}$	26.988 $\frac{1}{5}$	22.221 $\frac{875}{100}$	1.3	20.638 20.625	27.000 26.979	14 700	23 800	19 000	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173085
Diam. intérieur	20.64 mm
Diam. intérieur	13/16" inch
Diam. extérieur	26.99 mm
Diam. extérieur	1 1/16" inch
Epaisseur	22.22 mm
Epaisseur	0.875" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE