


Douille à aiguilles BAM1412-IKO - BAM1412-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	BAM 1412	26	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic	Basic static	Allowable	Assembled	
F_w	D	C	r_2	Shaft dia. h_6		Housing bore dia. J_7	load rating C	load rating C_0	rotational speed ⁽¹⁾	inner ring	
mm	mm	mm	mm	Max.	Min.	Max.	N	N	rpm		
22.225	28.575	19.05	2.8	22.225	22.212	28.587	28.566	12 800	20 400	18 000	IRB 1012

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173139
Diam. intérieur	22.23 mm
Diam. extérieur	28.58 mm
Épaisseur	19.05 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE