


Douille à aiguilles BAM1418-IKO - BAM1418-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam1418-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g			Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
22.225 (7/8)	—	—	—	—	—	—	BAM 1418			37	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	r_2 Max.	Shaft dia. h_6 Max.	Housing bore dia. J_7 Min.	Max.	C N	C_0 N	rpm	—
22.225	28.575	28.58(1.125)	2.8	22.225	22.212	28.587	28.566	19 800	35 600	18 000

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173160
Diam. intérieur	22.23 mm
Diam. extérieur	28.58 mm
Épaisseur	28.58 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE