


Douille à aiguilles BAM1422-IKO - BAM1422-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam1422-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
22.225 (7/8)	—	—	—	—	—	—	—	—	—	BAM 1422	44.5	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic	Basic static	Allowable	Assembled	
F_w	D	C	r_2	Shaft dia. h6		Housing bore dia. J7	load rating C	load rating C_0	rotational speed ⁽¹⁾	inner ring	
mm	mm	mm	mm	Max.	Min.	Max.	N	N	rpm		
22.225	28.575	34.92(1.375)	2.8	22.225	22.212	28.587	28.566	24 100	45 700	18 000	IRB 1022

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173177
Diam. intérieur	22.23 mm
Diam. extérieur	28.58 mm
Épaisseur	34.92 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE