


Douille à aiguilles BAM158-IKO - BAM158-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam158-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g			Grease retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Mass (Ref.) g		
23.812 ($\frac{9}{16}$)	—	—	—	—	—	—	BAM 158	19	—	—

Boundary dimensions mm (inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring		
F _w	D	C	Shaft dia. h _s	Housing bore dia. J7	h _s						
23.812	$\frac{30.162}{16}$	12.70	2.8	23.812	23.799	30.176	30.151	8 000	11 400	16 000	—

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173221
Diam. intérieur	23.81 mm
Diam. intérieur	15/16" inch
Diam. extérieur	30.16 mm
Diam. extérieur	1 3/16" inch
Epaisseur	12.7 mm
Epaisseur	1/2" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE