


## Douille à aiguilles BAM1614-IKO - BAM1614-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam1614-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g		
25.400 (1)	—	—	—	—	—	—	—	<b>BAM 1614</b>	33.5	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
<i>F<sub>w</sub></i>	<i>D</i>	<i>C</i>	<i>t<sub>1</sub></i> Max	Shaft dia. <i>h<sub>s</sub></i> Max.   Min.	Housing bore dia. <i>J<sub>7</sub></i> Max.   Min.		N	N	rpm		
25.400	31.750	22.22	0.875	25.400   25.387	31.764   31.739		16 900	30 400	15 000	<b>IRB 1214</b>	

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173252
Diam. intérieur	25.4 mm
Diam. extérieur	31.75 mm
Épaisseur	22.22 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE