


Douille à aiguilles BAM168-IKO - BAM168-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam168-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
25.400 (1)	—	—	—	—	—	BAM 168	—	20.5	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	Shaft dia. h _s	Housing bore dia. J7	Max.	Min.	N	N	rpm	
25.400	31.750	12.700	25.400	25.387	31.764	31.739	8 240	12 000	15 000	IRB 128

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173306
Diam. intérieur	25.4 mm
Diam. extérieur	31.75 mm
Épaisseur	12.7 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE