

Douille à aiguilles BAM208-IKO - BAM208-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam208-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
31.750 (1 1/4)	—	—	—	—	—	—	—	BAM 208	26	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynam. load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring		
F_w	D	C	t_1 Max.	Shaft dia. d_s Max. Min.	Housing bore dia. d_H Max. Min.	C N	C_0 N	rpm	IRB 168		
31.750 1 1/4	38.100 1 1/2	12.700 500	2.8	31.750 31.734	38.114 38.089	9 100	14 700	12 000	IRB 168		

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173405
Diam. intérieur	31.75 mm
Diam. intérieur	1 1/4" inch
Diam. extérieur	38.1 mm
Diam. extérieur	1 1/2" inch
Epaisseur	12.7 mm
Epaisseur	1/2" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE