


## Douille à aiguilles BAM76-IKO - BAM76-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam76-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
11.112 ( $\frac{7}{16}$ )	—	—	—	—	—	—	<b>BAM 76</b>	5.3	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. $h_8$		Housing bore dia. $J_7$		$C$	$C_0$	rpm	
			Max.	Min.	Max.	Min.	N	N		
11.112	15.875	9.52	11.112	11.101	15.885	15.867	3 290	3 470	35 000	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173535
Diam. intérieur	11.11 mm
Diam. extérieur	15.88 mm
Épaisseur	9.52 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE