


## Douille à aiguilles BAM95-IKO - BAM95-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/douille/bam95-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ( $\frac{9}{16}$ )	—	—	—	—	—	<b>BAM 95</b>	5.8	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
$F_w$	$D$	$C$	$b_2$	Shaft dia. h8	Housing bore dia. J7	$C$	$C_0$	rpm	
14.288	19.050	7.92	1.3	Max. 14.288 Min. 14.277	Max. 19.062 Min. 19.041	2 780	2 970	30 000	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173641
Diam. intérieur	14.29 mm
Diam. extérieur	19.05 mm
Épaisseur	7.92 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE