

## Roulement à rouleaux NCF2944CV-SKF - NCF2944CV-SKF

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/rouleaux/ncf2944cv-skf>

Dimensions d'encombrement			Charges de base		Vitesses de base		Designation
d	D	B	dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite	
mm			kN				
220	300	48	550	1060	950	1200	NCF 2944 CV

  

Technical drawing showing dimensions and calculation coefficients for the NCF2944CV roller bearing. The drawing includes a side view and a cross-section view. Dimensions shown include: d = 220 mm, D = 300 mm, B = 48 mm, d<sub>1</sub> = 214 mm, d<sub>2</sub> = 247 mm, f<sub>1</sub> = 2.3 mm, f<sub>2</sub> = 2.1 mm, e = 3 mm, D<sub>1</sub> = 289 mm, D<sub>2</sub> = 289 mm, D<sub>1</sub> = 231 mm, D<sub>2</sub> = 243 mm. Calculation coefficients: f<sub>1</sub> = 2, f<sub>2</sub> = 2, k<sub>1</sub> = 5.2, k<sub>2</sub> = 0.3, Y = 0.4.

### CARACTÉRISTIQUES PRODUIT

Marque	SKF
N° Ean13	7316572382073
Diam. intérieur	220 mm
Diam. extérieur	300 mm
Epaisseur	48 mm
Vitesse limite	1200 rpm
Poids	9888 g
Charge dynamique	550 kN
Charge statique	1060 kN
Conditionnement	-
Norme	-

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE