

Rotule GE GE80-HO-2RS-DURBAL - GE80-HO-2RS-DURBAL


<https://www.123roulement.be/roulement-palier/rotule/ge/ge80-ho-2rs-durbal>

GE80-HO-2RS



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:

steel / steel

Inner ring: bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring: bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication: lubrication required

order number	d	B	C	d ₁ min	D
GE 80 HO-2RS	80	74	45	90,0	120

type	measurement [mm]		d ₂	α [°]	load rating C ₁₀ [kN]	weight [kg]
	r ₁₅ min	r ₂₅ min				
GE 80 HO-2RS	0,3	1,0	105,0	3	2000	2,400

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952285863
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	120 mm
Diam. extérieur	4.724" inch
Epaisseur	45 mm
Epaisseur	1.772" inch
Type	GE
Poids	2400 g
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE