

Rondelle de butée WS1831-IKO - WS1831-IKO

<https://www.123roulement.be/accessoire/rondelle/rondelle-butee/ws1831-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings

| Shaft dia. mm | Identification number | | | | | | |
|------------------|------------------------------|---------------|---------------|---------------|------------|------------|---------------|
| | Thrust needle roller bearing | Mass (Ref.) g | Thrust washer | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 18 | NTB 1831 | 4.7 | AS 1831 | 3.9 | WS 1831 | GS 1831 | 10.7 |

| Boundary dimensions mm | | | | | | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | |
|---------------------------|----|----------------|---|------|--|----------------|--|--|--|--------|
| d | D | D _w | s | B | r _s max (⁽¹⁾) | C _i | | | | |
| 18 | 31 | 2 | 1 | 2.75 | 0.3 | 21 | 29 | 9 550 | 34 400 | 10 000 |

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952298900 |
| Diam. intérieur | 18 mm |
| Diam. extérieur | 31 mm |
| Épaisseur | 2.75 mm |
| Matière | ACIER |
| Poids | 10 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE