


Rondelle de butée WS3552-IKO - WS3552-IKO

<https://www.123roulement.be/accessoire/rondelle/rondelle-butee/ws3552-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings



Shaft dia. mm	Identification number						
	Thrust needle roller bearing	Mass (Ref.) g	Thrust washer	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
35	NTB 3552	10.6	AS 3552	8.9	WS 3552	GS 3552	31.5

d	Boundary dimensions mm						Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	
	D	D _w	s	B	r _s min ⁽¹⁾	C _i				
35	52	2	1	3.5	0.6	39	50	16 300	81 900	5 500

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952299068
Diam. intérieur	35 mm
Diam. extérieur	52 mm
Épaisseur	3.5 mm
Matière	ACIER
Poids	31 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE