

## Roulement conique 16579-16522-TIMKEN - 16579-16522-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/16579-16522-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Static <sup>2)</sup> C <sub>0</sub>	Dynamic <sup>3)</sup> C <sub>2</sub>	Static <sup>4)</sup> C <sub>0</sub>	Factor <sup>5)</sup> K	Static <sup>6)</sup> C <sub>0</sub>	Inner	Outer
mm	mm	mm	N	N	N	N		N		
31.750	68.262	22.225	46700	15200	17960	8150	2.12	7980	1629	16522
1.250	2.6875	0.8750			3830	1030		17000		

  

Bearing Dimensions										Geometry Factors		Bearing Weight	
Shaft					Housing			Cage		G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>1)</sup>	Max. Shaft Fillet Radius R <sup>2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sup>3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>4)</sup>	A <sub>2</sub> <sup>5)</sup>					
22.225	17.462	-3.4	1.5	37.5	0.8	63.0	61.0	8.8	1.6	22.7	13.0	0.9650	0.29
0.8750	0.6675	-0.29	0.36	1.48	1.58	0.02	2.49	2.40	0.02	0.06			0.05

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952308586
Diam. intérieur	31.75 mm
Diam. extérieur	68 mm
Épaisseur	22 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE