

## Roulement conique 2586-2525-TIMKEN - 2586-2525-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/2586-2525-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> e	Factor <sup>3)</sup> Y	Dynamic <sup>4)</sup> C <sub>90</sub>	Factor <sup>5)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N			N		N			
30.000	72.022	23.812	82700	2.37	2.19	21700	10200	2.14	94000	2586	2525
1.1811	2.8355	0.9375	18500			4880	2200		23200		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α <sup>6)</sup>	Max. Shaft Fillet Radius R <sup>7)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sup>8)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>9)</sup>	A <sub>2</sub> <sup>10)</sup>	A <sub>3</sub> <sup>11)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				mm
25.267	19.050	-0.4	3.5	36.0	42.5	0.8	65.0	62.0	0.8	0.8	25.6	9.6	0.9050	6.90
0.9953	0.7500	-0.34	0.14	1.42	1.67	0.03	2.56	2.48	0.03	0.04				1.10

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952309224
Diam. intérieur	30 mm
Diam. extérieur	72.02 mm
Épaisseur	23.81 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE