


Roulement conique 2561X-2523-TIMKEN - 2561X-2523-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/2561x-2523-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|--------|---------|--|----------------------------|---|----------------------------|--------------------------|-------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ f | Dynamic ⁽³⁾ C ₁₀ | Factor ⁽⁴⁾ K | Static C ₂ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 30.213 | 69.850 | 23.812 | 83700 | 0.37 | 21700 | 2.14 | 84600 | 2561X | 2523 | |
| 1.1895 | 2.7500 | 0.9375 | | | 4800 | | 21200 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|--------------------------|---|--------------------------------------|---|--------------------------------------|-------------------------------|-------------------------------|--------|------------------|----------------|----------------|----------------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | |
| Width B | Width C | ER. Dr. a ⁽¹⁾ | Max. Shaft Fillet Radius R ⁽²⁾ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ⁽³⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽⁴⁾ | A ₂ ⁽⁵⁾ | Cage | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | |
| 24.714 | 19.950 | -0.8 | 2.3 | 36.5 | 40.8 | 1.3 | 64.0 | 61.8 | 8.8 | | | | |
| 0.9730 | 0.7900 | -0.34 | 0.09 | 1.44 | 1.57 | 0.05 | 2.52 | 2.40 | 0.35 | | | | |
| | | | | | | | | | 1.5 | | | | |
| | | | | | | | | | 0.06 | | | | |
| | | | | | | | | | 25.0 | | | | |
| | | | | | | | | | 5.8 | | | | |
| | | | | | | | | | 0.9058 | | | | |
| | | | | | | | | | 0.46 | | | | |
| | | | | | | | | | 1.02 | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952309903 |
| Diam. intérieur | 30.21 mm |
| Diam. intérieur | 1.189" inch |
| Diam. extérieur | 69.85 mm |
| Diam. extérieur | 2 3/4" inch |
| Epaisseur | 23.81 mm |
| Epaisseur | 15/16" inch |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE