


## Roulement conique 4375-4335-TIMKEN - 4375-4335-TIMKEN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/4375-4335-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |        |         | Load Ratings                             |                            |  |                            |                          |       | Part Number |      |      |
|--------------------|--------|---------|--|----------------------------|--|----------------------------|--------------------------|-------|-------------|------|------|
| Bore d             | O.D. D | Width T | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factor <sup>(2)</sup><br>Y | Dynamic <sup>(3)</sup><br>C <sub>2</sub> | Factor <sup>(4)</sup><br>K | Static<br>C <sub>0</sub> | Inner | Outer       |      |      |
| mm                 | mm     | mm      | N  |                            | N  |                            | N                        |       |             |      |      |
| 38.100             | 90.488 | 39.688  | 109000                                   | 2.70                       | 2.11                                     | 51900                      | 25700                    | 2.05  | 294000      | 4375 | 4335 |
| 1.500              | 3.5625 | 1.5625  | 44700                                    |                            |  | 11600                      | 5040                     |       | 45800       |      |      |

| Bearing Dimensions |         |            |  |                                      |  |                                      |                               |                               |                               | Geometry Factors |                |                | Bearing Weight |                |
|--------------------|---------|------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|----------------|
| Shaft              |         |            |  |                                      | Housing                                  |                                      |                               |                               |                               | C <sub>1</sub>   | C <sub>2</sub> | C <sub>3</sub> |                |                |
| Width B            | Width C | ER. Dr. μm | Max Shaft Fillet Radius R <sub>1</sub> | Backing Shoulder Dia. d <sub>1</sub> | Max Housing Fillet Radius r <sub>1</sub> | Backing Shoulder Dia. D <sub>1</sub> | A <sub>1</sub> <sup>(1)</sup> | A <sub>2</sub> <sup>(1)</sup> | A <sub>3</sub> <sup>(1)</sup> |                  |                |                | G <sub>1</sub> | G <sub>2</sub> |
| mm                 | mm      | mm         | mm                                     | mm                                   | mm                                       | mm                                   | mm                            | mm                            | mm                            |                  |                |                | kg             |                |
| 40.386             | 33.338  | -15.8      | 1.5                                    | 53.8                                 | 53.8                                     | 3.3                                  | 85.9                          | 77.8                          | 2.2                           | 8.6              | 52.9           | 14.3           | 0.0072         | 1.31           |
| 1.5900             | 1.3125  | -0.59      | 0.06                                   | 2.01                                 | 2.09                                     | 0.13                                 | 3.35                          | 3.03                          | 0.09                          | 0.03             |                |                | 2.89           |                |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | TIMKEN        |
| N° Ean13        | 3663952312187 |
| Diam. intérieur | 38.1 mm       |
| Diam. intérieur | 1 1/2" inch   |
| Diam. extérieur | 90.488 mm     |
| Diam. extérieur | 3 9/16" inch  |
| Epaisseur       | 39.688 mm     |
| Epaisseur       | 1 9/16" inch  |
| Poids           | 1310 g        |
| Conditionnement | 1             |
| Norme           | Sans norme    |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE